

ENVIRONMENTAL PRODUCT DECLARATION

In accordance with ISO 14025 and EN 15804+A2

SCHWENK Zement GmbH & Co. KG – 2023 Portlandkalksteinzement CEM II/A-LL 42,5 N Karlstadt 0840-CPR-3020-246100-15





Owner of the declaration

SCHWENK Zement GmbH & Co. KG Hindenburgring 15 89077 Ulm Germany

Product

2023 Portlandkalksteinzement CEM II/A-LL 42,5 N Karlstadt 0840-CPR-3020-246100-15

Declared product / Declared unit

1t of 2023 Portlandkalksteinzement CEM II/A-LL 42,5 N Karlstadt 0840-CPR-3020-246100-15

This declaration is based on Product Category Rules

EN 15804:2012 + A2:2019, EN 16908:2017+A1:2022: Cement and building lime - Environmental product declarations - Product category rules complementary to EN 15804

Program operator:

EPD-Norge Majorstuen P.O. Box 5250 N-0303 Oslo Norway

Declaration number NEPD-10023-10023-2

Registration number NEPD-10023-10023-2

Issue date 19.02.2025

Valid to 18.02.2030

EPD Software Emidat EPD Tool v1.0.0

General Information

Product

2023 Portlandkalksteinzement CEM II/A-LL 42,5 N Karlstadt 0840-CPR-3020-246100-15

Program Operator

EPD-Norge Majorstuen P.O. Box 5250 N-0303 Oslo Norway Phone: +47 23 08 80 00 Email: post@epd-norge.no

Declaration Number

NEPD-10023-10023-2

This declaration is based on Product Category Rules EN 15804:2012 + A2:2019,

EN 16908:2017+A1:2022: Cement and building lime -Environmental product declarations - Product category rules complementary to EN 15804

Statements

The owner of the declaration shall be liable for the underlying information and evidence. EPD Norway shall not be liable with respect to manufacturer, life cycle assessment data and evidences.

Declared unit

1 t of 2023 Portlandkalksteinzement CEM II/A-LL 42,5 N Karlstadt 0840-CPR-3020-246100-15

General information on verification of EPD from EPD tools

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Verification of each EPD is made according to EPDNorway's guidelines for verification and approval requiring that tools are i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPD-Norway, and iii) the process is reviewed annually by an independent third party verifier. See Appendix G of EPD-Norway's General Programme Instructions for further information on EPD tools.

Verification of EPD tool

Charlotte Merlin, FORCE Technology (no signature required)

Owner of the declaration SCHWENK Zement GmbH & Co. KG

Contact person info@schwenk.de

Phone

+497319341-0

Email info@schwenk.de

Manufacturer SCHWENK Zement GmbH & Co. KG Hindenburgring 15 89077 Ulm, Germany

Place of production Karlstadt, Germany

Management system ISO 9001, ISO 14001, ISO 50001

Organisation no Registereintragung: HRA 1955, Amtsgericht Ulm

Issue date 19.02.2025

Valid to 18.02.2030

Year of study 2023

Comparability

EPDs of construction products may not be comparable if they do not comply with EN 15804 and are not seen in a building context. EPD data may not be comparable if the datasets used are not developed in accordance with EN 15804 and if the background systems are not based on the same database (including primary and secondary data).

Development and verification of EPD

The declaration was created using the Emidat EPD tool v1.0, developed by Emidat GmbH. The EPD tool has been approved by EPD Norway.

Developer of EPD: Dr. Klaus Raiber Reviewer of company-specific input data and EPD: Thomas Arndt


Approved

Håkon Hauan, CEO EPD-Norge

Product

Product description

Cement is a hydraulically hardening binder for the production of concrete and mortar. It is a mixture of finely ground, non-metallic and inorganic components. After adding water to the cement, a suspension (cement paste) is formed, which solidifies and hardens both in air and under water due to the hydration reaction that then begins and remains permanently solid. The composition of the product complies with the specifications of EN 197-1.



Cement is the key ingredient in concrete. When mixed with water and aggregates such as sand and gravel, it forms a paste that binds the aggregates together to create concrete, the most widely used construction material in the world.

Cement can also be mixed with sand and water to create mortar or grout, used as a bonding agent between bricks, stones, or concrete blocks in masonry construction. Cement can also be used to stabilise and improve the properties of soil in construction projects. Soil-cement mixtures are created by mixing cement with soil to increase its strength, durability, and load-bearing capacity. This technique is commonly used in road construction, building foundations, and slope stabilisation.

Product specification

Name of ingredient	Share of total weight	Country of origin
Anhydrite	0 - 6 %	Germany
Clinker	65 - 80 %	Germany
Ferrous sulphate	0 - 6 %	Germany
Grinding aid	0 - 6 %	Germany
Gypsum	0 - 6 %	Germany
Natural aggregates	20 - 35 %	Germany

Technical data

	Unit	Value
Compressive Strength (Prisms, EN 196-1)	N / mm²	42.5
Density	kg / m³	3000.0

Market

Germany

Reference service life


This study does not cover the use stage. Thus, the reference service life is irrelevant.

LCA: Calculation rules

Declared unit

1 t of 2023 Portlandkalksteinzement CEM II/A-LL 42,5 N Karlstadt 0840-CPR-3020-246100-15

System boundary



Data quality

The Emidat EPD Tool v1.0.0 was used for LCA modeling and calculation. Background data was used from ecoinvent database v3.10.



System boundaries (X=included, MND=module not declared)

	Pro	oducti	ion	Instal	lation			U	se stag	ge				End-o	of-Life		Next product system
	Raw material supply	Transport	Manufacturing	Transport	Installation Process	Use	Maintenance	Repair	Replacement	Refurbishment	Operational Energy Use	Operational Water Use	Demolition	Transport	Waste Processing	Disposal	Benefits and loads beyond the system boundary
Module	A1	A2	A3	A4	A5	B1	B2	В3	B4	B5	B6	B7	C1	C2	C3	C4	D
Modules declared	x	x	x	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND
Geography			DE	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND

For the geographies modeled in A1 and A2, refer to *Product specification*.

Type of EPD: cradle to gate (A1-A3) **Stage of Material Production and Construction** Module A1: Extraction and processing of cement raw materials Module A2: Transportation of raw materials to the cement plant Module A3: Cement production at the plant and waste treatment

Cut-off criteria

No cut-offs were applied.

Allocation

Elementary flows (energy and fuels, ancillary materials and waste) data was collected on production-process-level. Using the total output of the production process in 2023, elementary flows are assigned to 1 declared unit based on mass.

LCA: Results

Core environmental impact indicators

Indicator	Unit	A1-3
GWP-total	kg CO₂-eq.	6.61e+02 (4.32e+02)*
GWP-fossil	kg CO₂-eq.	5.68e+02 (4.28e+02)*
GWP-biogenic	kg CO₂-eq.	9.31e+01 (3.52e+00)*
GWP-luluc	kg CO ₂ -eq.	6.84e-02
ODP	kg CFC-11-Eq	4.47e-07
AP	mol H+-Eq	1.00e+00
EP-freshwater	kg P-Eq	5.65e-02
EP-marine	kg N-Eq	1.91e-01
EP-terrestrial	mol N-Eq	2.23e+00
POCP	kg NMVOC-Eq	6.29e-01
ADPE	kg Sb-Eq	1.94e-03
ADPF	MJ, net calorific value	2.44e+03
WDP	m ³ world Eq deprived	1.02e+01

GWP-total: Global Warming Potential - total **GWP-fossil**: Global warming potential - fossil **GWP-biogenic**: Global Warming Potential - biogenic **GWP-luluc**: Global Warming Potential - luluc **ODP**: Depletion potential of the stratospheric ozone layer **AP**: Acidification potential, Accumulated Exceedance **EP-freshwater**: Eutrophication potential - freshwater **EP-marine**: Eutrophication potential - marine **EP-terrestrial**: Eutrophication potential - terrestrial **POCP**: Photochemical Ozone Creation Potential **ADPE**: Abiotic depletion potential - non-fossil resources **ADPF**: Abiotic depletion potential - fossil resources **WDP**: Water (user) deprivation potential

* The first value is the gross value, it includes the impacts from all manufacturing activities. Gross values are more commonly used in Northern Europe. The value in brackets is the net value, it excludes the impact from the incineration of waste-derived fuels, and is more common in Central Europe and Germany.

Additional indicators

Indicator	Unit	A1-3
РМ	disease incidence	6.22e-06
IRP	kBq U235-Eq	8.27e+00
ETP-fw	CTUe	2.17e+02
HTP-c	CTUh	1.18e-07
HTP-nc	CTUh	2.93e-06
SQP	dimensionless	1.24e+02

PM: Potential incidence of disease due to PM emissions **IRP**: Potential Human exposure efficiency relative to U235 **ETP-fw**: Potential Comparative Toxic Unit for ecosystems **HTP-c**: Potential Comparative Toxic Unit for humans - cancer effects **HTP-nc**: Potential Comparative Toxic Unit for humans - non-cancer effects **SQP**: Potential Soil quality index

IRP: This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator. **ETP-fw**, **HTP-c**, **HTP-nc** and **SQP**: The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experienced with these indicators.

Use of resources

Indicator	Unit	A1-3
PERE	MJ	8.86e+02
PERM	MJ	0
PERT	MJ	8.86e+02
PENRE	MJ	2.43e+03
PENRM	MJ	1.26e+01
PENRT	MJ	2.44e+03
SM	kg	2.61e+01
RSF	MJ	1.28e+03
NRSF	MJ	2.16e+03
FW	m³	3.37e-01

PERE: Primary energy resources - renewable: use as energy carrier **PERM**: Primary energy resources - renewable: used as raw materials **PERT**: Primary energy resources - non-renewable: use as energy carrier **PENRM**: Primary energy resources - non-renewable: use as energy carrier **PENRM**: Primary energy resources - non-renewable: used as raw materials **PENRT**: Primary energy resources - non-renewable: total **SM**: Use of secondary material **RSF**: Renewable secondary fuels **NRSF**: Non-renewable secondary fuels **FW**: Net use of fresh water

Waste flows

Indicator	Unit	A1-3
HWD	kg	1.44e+00
NHWD	kg	2.77e+02
RWD	kg	2.42e-03

HWD: Hazardous waste disposed NHWD: Non hazardous waste disposed RWD: Radioactive waste disposed

Output flows

Indicator	Unit	A1-3
CRU	kg	0
MFR	kg	0
MER	kg	0
EEE	MJ	0
EET	MJ	0

CRU: Components for re-use **MFR**: Materials for recycling **MER**: Materials for energy recovery **EEE**: Exported electrical energy **EET**: Exported thermal energy

Name	Value	Unit
Biogenic carbon content in product	0	kg C
Biogenic carbon content in accompanying packaging	0	kg C

Additional requirements

Greenhouse gas emissions from the use of electricity in the manufacturing phase

Electricity consumption in the manufacturing phase is composed from the source below. Electricity is represented by data in ecoinvent 3.10 regionalised for Germany.

Electricity	Unit	Value
Electricity from grid	kg CO₂-eq. / kWh	0.47

Dangerous substances

The product contains no substances given by the REACH candidate list.

Additional environmental information

Additional environmental impact indicators required in NPCR Part A for construction products

Indicator	Unit	A1-3
GWP-IOBC	kg CO₂-eq.	4.16e+02

GWP-IOBC: Global Warming Potential - Instantaneous oxidation of biogenic carbon

Bibliography

DIN EN ISO 14025:2011-10	Environmental labels and declarations - Type III environmental declarations - Principles and procedures
DIN EN ISO 14040:2021-02	Environmental management - Life cycle assessment - Principles and framework
DIN EN ISO 14044:2021-02	Environmental management - Life cycle assessment - Requirements and guidelines
EN 15804:2012+A2:2019	Sustainability of construction works - Environmental product declarations - Core rules for the product category of construction products
DIN CENTR 15941:2010-11	Sustainability of construction works - Environmental product declarations - Methodology for selection and use of generic data
DIN EN 15942:2022-04	Sustainability of construction works - Environmental product declarations - Communication format business-to-business
ISO 21930:2017-07	Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products and services
Ecoinvent v3.10	ecoinvent, Zurich, Switzerland, database version 3.10
PCR	EN 16908:2017+A1:2022: Cement and building lime - Environmental product declarations - Product category rules complementary to EN 15804
EN 16908:2017+A1:2022	Cement and building lime - Environmental product declarations - Product category rules complementary to EN 15804
	Pasia principles and recommendations for describing the dismontling past use, and dispessel stage of

Basic principles and recommendations for describing the dismantling, post use, and disposal stage of construction products: https://www.umweltbundesamt.de/sites/default/files/medien/1410/publikationen/2020-07-06_texte_130-2020_guidance-document-construction-industry.pdf

 $\label{eq:licb-handbook-lcIA-Background-analysis-online-12 March 2010.pdf} ILCD-Handbook-LCIA-Background-analysis-online-12 March 2010.pdf$

	Program Operator	Phone	+47 23 08 80 00
Colobal Program Operator	EPD-Norge	1 Hone	
	Majorstuen P.O. Box 5250, N-0303 Oslo	Email	post@epd-norge.no
	Norway	Web	www.epd-norge.no
Colobal Program Operator	Publisher	Phone	+47 23 08 80 00
	The Norwegian EPD Foundation		
	Post Box 5250 Majorstuen, 0303 Oslo	Email	post@epd-norge.no
	Norway	Web	www.epd-norge.no
	Owner of the declaration	Phone	+497319341-0
SCHWENK Baustoff leben	SCHWENK Zement GmbH & Co. KG		
	Hindenburgring 15, 89077 Ulm	Email	info@schwenk.de
	Germany	Web	https://www.schwenk.de
	Author of the life cycle assesment	Phone	+497319341-0
🗑 SCHWENK	SCHWENK Zement GmbH & Co. KG		
Baustoff leben	Hindenburgring 15, 89077 Ulm	Email	info@schwenk.de
	Germany	Web	https://www.schwenk.de
		Web	www.eco-platform.org
	ECO Platform		<u></u>
	ECO Portal	Web	ECO Portal
	Developer of EPD generator	Phone	+49 176 56 96 77 91
	Emidat GmbH		
	Sandstraße 33, 80335 München	Email	epd@emidat.com
	Germany	Web	www.emidat.com