

# ENVIRONMENTAL PRODUCT DECLARATION

In accordance with ISO 14025 and EN 15804+A2

## SCHWENK Zement GmbH & Co. KG CEM II/B-P 42,5 N - Mergelstetten - 0840-CPR-3030-243200-15



🗑 SCHWENK

#### Owner of the declaration

SCHWENK Zement GmbH & Co. KG Hindenburgring 15 89077 Ulm Germany

Product CEM II/B-P 42,5 N - Mergelstetten - 0840-CPR-3030-243200-15

Declared product / Declared unit 1t of CEM II/B-P 42,5 N - Mergelstetten -0840-CPR-3030-243200-15

## This declaration is based on Product Category Rules

EN 15804:2012 + A2:2019, EN 16908:2017+A1:2022: Cement and building lime - Environmental product declarations - Product category rules complementary to EN 15804

#### Program operator:

EPD Norway Majorstuen P.O. Box 5250 N-0303 Oslo Norway

Declaration number NEPD-10098-10098-2

Registration number NEPD-10098-10098-2

**Issue date** 07.04.2025

Valid to 06.04.2030

EPD Software Emidat EPD Tool v1.0.0

## **General Information**

#### Product

CEM II/B-P 42,5 N - Mergelstetten - 0840-CPR-3030-243200-15

## **Program Operator**

EPD Norway Majorstuen P.O. Box 5250 N-0303 Oslo Norway Phone: +47 23 08 80 00 Email: post@epd-norge.no

#### **Declaration Number**

NEPD-10098-10098-2

## This declaration is based on Product Category Rules EN 15804:2012 + A2:2019,

EN 16908:2017+A1:2022: Cement and building lime -Environmental product declarations - Product category rules complementary to EN 15804

## Statements

The owner of the declaration shall be liable for the underlying information and evidence. EPD Norway shall not be liable with respect to manufacturer, life cycle assessment data and evidences.

## **Declared unit**

1 t of CEM II/B-P 42,5 N - Mergelstetten - 0840-CPR-3030-243200-15

# General information on verification of EPD from EPD tools

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Verification of each EPD is made according to EPDNorway's guidelines for verification and approval requiring that tools are i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPD-Norway, and iii) the process is reviewed annually by an independent third party verifier. See Appendix G of EPD-Norway's General Programme Instructions for further information on EPD tools.

### Verification of EPD tool

Charlotte Merlin, FORCE Technology (no signature required)

Owner of the declaration SCHWENK Zement GmbH & Co. KG Contact person info@schwenk.de

**Phone** +497319341-0

Email info@schwenk.de

Manufacturer SCHWENK Zement GmbH & Co. KG Hindenburgring 15 89077 Ulm, Germany

Place of production Heidenheim-Mergelstetten , Germany

Management system ISO 9001, ISO 14001, ISO 50001

Organisation no Registereintragung: HRA 1955, Amtsgericht Ulm

**Issue date** 07.04.2025

Valid to 06.04.2030

Year of study 2023

## Comparability

EPDs of construction products may not be comparable if they do not comply with EN 15804 and are not seen in a building context. EPD data may not be comparable if the datasets used are not developed in accordance with EN 15804 and if the background systems are not based on the same database (including primary and secondary data).

### **Development and verification of EPD**

The declaration was created using the Emidat EPD tool v1.0, developed by Emidat GmbH. The EPD tool has been approved by EPD Norway.

Developer of EPD: Dr. Klaus Raiber Reviewer of company-specific input data and EPD: Thomas Arndt


Approved

Håkon Hauan, CEO EPD-Norge

## Product

## **Product description**

Cement is a hydraulically hardening binder for the production of concrete and mortar. It is a mixture of finely ground, non-metallic and inorganic components. After adding water to the cement, a suspension (cement paste) is formed, which solidifies and hardens both in air and under water due to the hydration reaction that then begins and remains permanently solid. The composition of the product complies with the specifications of EN 197-1.



Cement is the key ingredient in concrete. When mixed with water and aggregates such as sand and gravel, it forms a paste that binds the aggregates together to create concrete, the most widely used construction material in the world.

Cement can also be mixed with sand and water to create mortar or grout, used as a bonding agent between bricks, stones, or concrete blocks in masonry construction. Cement can also be used to stabilise and improve the properties of soil in construction projects. Soil-cement mixtures are created by mixing cement with soil to increase its strength, durability, and load-bearing capacity. This technique is commonly used in road construction, building foundations, and slope stabilisation.

## **Product specification**

Name of ingredient	Share of total weight	Country of origin
Additives	0 - 6 %	Germany
Admixtures	0 - 6 %	Germany
Clinker	65 - 80 %	Germany
Gypsum	0 - 6 %	Germany
Mineral materials	20 - 35 %	Germany
Natural aggregates	0 - 6 %	Germany

## **Technical data**

	Unit	Value
Compressive Strength (Prisms, EN 196-1)	N / mm²	42.5
Density	kg / m³	2900.0

## Market

Germany

#### **Reference service life**

This study does not cover the use stage. Thus, the reference service life is irrelevant.


## LCA: Calculation rules

## **Declared unit**

1 t of CEM II/B-P 42,5 N - Mergelstetten - 0840-CPR-3030-243200-15

## System boundary

System boundary (A1-A3)



## **Data quality**

The Emidat EPD Tool v1.0.0 was used for LCA modeling and calculation. Background data was used from ecoinvent database v3.10.

## System boundaries (X=included, MND=module not declared)

	Pro	oducti	ion	Instal	stallation Use stage			End-of-Life			Next product system						
	Raw material supply	Transport	Manufacturing	Transport	Installation Process	Use	Maintenance	Repair	Replacement	Refurbishment	Operational Energy Use	Operational Water Use	Demolition	Transport	Waste Processing	Disposal	Benefits and loads beyond the system boundary
Module	A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Modules declared	х	x	х	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND
Geography			DE	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND

For the geographies modeled in A1 and A2, refer to *Product specification*.

Type of EPD: cradle to gate (A1-A3) **Stage of Material Production and Construction** Module A1: Extraction and processing of cement raw materials Module A2: Transportation of raw materials to the cement plant Module A3: Cement production at the plant and waste treatment

## **Cut-off criteria**

No cut-offs were applied.

## Allocation

Elementary flows (energy and fuels, ancillary materials and waste) data was collected on production-process-level. Using the total output of the production process in 2023, elementary flows are assigned to 1 declared unit based on mass.

## LCA: Results

### **Core environmental impact indicators**

Indicator	Unit	A1-3
GWP-total	kg CO₂-eq.	6.37e+02 (4.19e+02)*
GWP-fossil	kg CO <sub>2</sub> -eq.	5.57e+02 (4.15e+02)*
GWP-biogenic	kg CO₂-eq.	8.00e+01 (4.09e+00)*
GWP-Iuluc	kg CO <sub>2</sub> -eq.	7.89e-02
ODP	kg CFC-11-Eq	4.80e-07
AP	mol H+-Eq	4.42e-01
EP-freshwater	kg P-Eq	6.45e-02
EP-marine	kg N-Eq	1.86e-01
EP-terrestrial	mol N-Eq	2.13e+00
POCP	kg NMVOC-Eq	4.96e-01
ADPE	kg Sb-Eq	2.93e-03
ADPF	MJ, net calorific value	2.56e+03
WDP	m³ world Eq deprived	1.09e+01

GWP-total: Global Warming Potential - total GWP-fossil: Global warming potential - fossil GWP-biogenic: Global Warming Potential - biogenic GWP-luluc: Global Warming Potential - luluc ODP: Depletion potential of the stratospheric ozone layer AP: Acidification potential, Accumulated Exceedance EP-freshwater: Eutrophication potential - freshwater EP-marine: Eutrophication potential - marine EP-terrestrial: Eutrophication potential - terrestrial POCP: Photochemical Ozone Creation Potential ADPE: Abiotic depletion potential - non-fossil resources ADPF: Abiotic depletion potential - fossil resources WDP: Water (user) deprivation potential

\* The first value is the gross value, it includes the impacts from all manufacturing activities. Gross values are more commonly used in Northern Europe. The value in brackets is the net value, it excludes the impact from the incineration of waste-derived fuels, and is more common in Central Europe and Germany.

## **Additional indicators**

Indicator	Unit	A1-3
РМ	disease incidence	2.60e-06
IRP	kBq U235-Eq	9.48e+00
ETP-fw	CTUe	2.14e+02
HTP-c	CTUh	1.24e-07
HTP-nc	CTUh	1.98e-06
SQP	dimensionless	1.46e+02

PM: Potential incidence of disease due to PM emissions IRP: Potential Human exposure efficiency relative to U235 ETP-fw: Potential Comparative Toxic Unit for ecosystems HTP-c: Potential Comparative Toxic Unit for humans - cancer effects HTP-nc: Potential Comparative Toxic Unit for humans - non-cancer effects SQP: Potential Soil quality index

**IRP**: This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

**ETP-fw**, **HTP-c**, **HTP-nc** and **SQP**: The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experienced with these indicators.

## **Use of resources**

Indicator	Unit	A1-3
PERE	MJ	9.60e+02
PERM	MJ	0
PERT	MJ	9.60e+02
PENRE	MJ	2.55e+03
PENRM	MJ	4.38e+00
PENRT	MJ	2.56e+03
SM	kg	0
RSF	MJ	1.03e+03
NRSF	MJ	2.29e+03
FW	m³	3.37e-01

PERE: Primary energy resources - renewable: use as energy carrier PERM: Primary energy resources - renewable: used as raw materials PERT: Primary energy resources - renewable: total PENRE: Primary energy resources - non-renewable: use as energy carrier PENRM: Primary energy resources - non-renewable: used as raw materials PENRT: Primary energy resources - non-renewable: total SM: Use of secondary material RSF: Renewable secondary fuels NRSF: Non-renewable secondary fuels FW: Net use of fresh water

## Waste flows

Indicator	Unit	A1-3
HWD	kg	1.68e+00
NHWD	kg	3.15e+02
RWD	kg	2.78e-03

HWD: Hazardous waste disposed NHWD: Non hazardous waste disposed RWD: Radioactive waste disposed

## **Output flows**

Indicator	Unit	A1-3
CRU	kg	0
MFR	kg	0
MER	kg	0
EEE	MJ	0
EET	MJ	0

CRU: Components for re-use MFR: Materials for recycling MER: Materials for energy recovery EEE: Exported electrical energy EET: Exported thermal energy

Name	Value	Unit
Biogenic carbon content in product	0	kg C
Biogenic carbon content in accompanying packaging	0	kg C

## **Additional requirements**

## Greenhouse gas emissions from the use of electricity in the manufacturing phase

Electricity consumption in the manufacturing phase is composed from the source below. Electricity is represented by data in ecoinvent 3.10 regionalised for Germany.

Electricity	Unit	Value
Electricity from grid	kg CO <sub>2</sub> -eq. / kWh	0.47

## **Dangerous substances**

The product contains no substances given by the REACH candidate list.

## Additional environmental information

## Additional environmental impact indicators required in NPCR Part A for construction products

Indicator	Unit	A1-3	
GWP-IOBC	kg CO <sub>2</sub> -eq.	4.02e+02	

GWP-IOBC: Global Warming Potential - Instantaneous oxidation of biogenic carbon

## Bibliography

DIN EN ISO 14025:2011-10	Environmental labels and declarations - Type III environmental declarations - Principles and procedures
DIN EN ISO 14040:2021-02	Environmental management - Life cycle assessment - Principles and framework
DIN EN ISO 14044:2021-02	Environmental management - Life cycle assessment - Requirements and guidelines
EN 15804:2012+A2:2019	Sustainability of construction works - Environmental product declarations - Core rules for the product category of construction products
DIN CENTR 15941:2010-11	Sustainability of construction works - Environmental product declarations - Methodology for selection and use of generic data
DIN EN 15942:2022-04	Sustainability of construction works - Environmental product declarations - Communication format business-to-business
ISO 21930:2017-07	Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products and services
Ecoinvent v3.10	ecoinvent, Zurich, Switzerland, database version 3.10
PCR	EN 16908:2017+A1:2022: Cement and building lime - Environmental product declarations - Product category rules complementary to EN 15804
EN 16908:2017+A1:2022	Cement and building lime - Environmental product declarations - Product category rules complementary to EN 15804
	Design tripping and recommandations for describing the dismostling next use, and dispessed store of

Basic principles and recommendations for describing the dismantling, post use, and disposal stage of construction products: https://www.umweltbundesamt.de/sites/default/files/medien/1410/publikationen/2020-07-06\_texte\_130-2020\_guidance-document-construction-industry.pdf

 $\label{eq:licb-handbook-lcIA-Background-analysis-online-12 March 2010.pdf} ILCD-Handbook-LCIA-Background-analysis-online-12 March 2010.pdf$ 

	Program Operator	Phone	+47 23 08 80 00
Clobal Program Operator	EPD Norway		
	Majorstuen P.O. Box 5250, N-0303 Oslo	Email	post@epd-norge.no
	Norway	Web	www.epd-norge.no
Clobal Program Operator	Publisher	Phone	+47 23 08 80 00
	The Norwegian EPD Foundation		
	Post Box 5250 Majorstuen, 0303 Oslo	Email	post@epd-norge.no
	Norway	Web	www.epd-norge.no
SCHWENK	Owner of the declaration	Phone	+497319341-0
	SCHWENK Zement GmbH & Co. KG		
	Hindenburgring 15, 89077 Ulm	Email	info@schwenk.de
	Germany	Web	https://www.schwenk.de
SCHWENK	Author of the life cycle assesment	Phone	+497319341-0
	SCHWENK Zement GmbH & Co. KG		
	Hindenburgring 15, 89077 Ulm	Email	info@schwenk.de
	Germany	Web	https://www.schwenk.de
ECO PLATFORM	ECO Platform	Web	www.eco-platform.org
	ECO Portal	Web	ECO Portal
	Devialence of EDD semanator	Phone	+49 176 56 96 77 91
	Developer of EPD generator Emidat GmbH	Phone	+49 1/0 20 90 // 91
		Email	and@amidat.com
	Sandstraße 33, 80335 München	Web	epd@emidat.com www.emidat.com
	Germany	vveb	www.emidat.com