

**SECTION 1: Identification of the substance or mixture and of the company****1.1 Product identifier**

Hydraulic binders for soil improvement and soil stabilisation.

**Trade name**

|   |                          |  |                          |
|---|--------------------------|--|--------------------------|
| Bodenbinder 100<br>Bodenbinder B 10   | UFI: 35Y9-S08M-600R-UD42 | Bodenbinder 700<br>Bodenbinder B 70                  | UFI: Q82S-H06M-H006-GASH |
| Bodenbinder 300<br>Bodenbinder B 30   | UFI: 5E49-X06H-A008-DY9Q | Bodenbinder L  | UFI: VYX9-X1K5-U00Y-JRE2 |
| Bodenbinder 500<br>Bodenbinder B 50<br>Bodenbinder B 50 mit<br>hydrophoben Zusätzen | UFI: QNY4-Q0V1-V00X-5W6X | SCHWENK Recyclingbinder<br>Tragschichtbinder HRB E 4 | UFI: E920-00A7-4009-XQGG |
| SCHWENK Tragschichtbinder mit hydrophoben Zusätzen                                  |                          | UFI: FJT9-A229-G00Y-VD4W                             |                          |
| SCHWENK Zement mit hydrophoben Zusätzen   |                          | UFI: SJED-E189-200E-M86M                             |                          |

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Bodenbinder are used in industrial installations to manufacture/formulate hydraulic binders.

Common Bodenbinder and cement containing mixtures for soil improvement and soil stabilization (hydraulic binders) are used industrially, by professionals as well as by consumers in building and construction work, indoor and outdoor. The identified uses of Bodenbinder and cement containing mixtures cover the dry products and the products in a wet suspension (paste).

A list of uses for professional users, indicating the process categories and descriptors according to ECHA Guidance R.12 (ECHA-2010-G-05) are listed in section 16.

**1.3. Details of the supplier of the safety data sheet**

SCHWENK Zement GmbH & Co. KG, Werksgruppe Süd, Werk Allmendingen, Fabrikstraße, D-89604 Allmendingen  
Information telephone number: Department of Quality/Laboratory: +49 7391 581-0

SCHWENK Zement GmbH & Co. KG, Werksgruppe Nord, Werk Bernburg, Altenburger Chaussee 3, D-06406 Bernburg  
Information telephone number: Department of Quality/Laboratory: +49 3471 358-0

SCHWENK Zement GmbH & Co. KG, Werksgruppe Nord, Werk Karlstadt, Laudенbacher Weg 5, D-97753 Karlstadt  
Information telephone number: Department of Quality/Laboratory: +49 9351 797-0

SCHWENK Zement GmbH & Co. KG, Werksgruppe Süd, Werk Mergelstetten, Hainenbachstraße 30, D-89522 Heidenheim  
Information telephone number: Department of Quality/Laboratory: +49 7321 310-0

E-mail address of person responsible for the SDS: raiber.klaus@schwenk.de

**1.4. Emergency telephone number**

Emergency telephone number: +49 6131 19240 of the Giftnotrufzentrale Mainz  
Hours of operation: 24 h a day German and English

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****2.1.1 According to Regulation (EC) No 1272/2008**

| Hazard class  | Hazard category | Classification procedure  |
|---|-----------------|---------------------------|
| Skin irritation   | 2, H 315        | On the basis of test data |
| Serious eye damage/eye irritation   | 1, H 318        | On the basis of test data |
| Specific target organ toxicity single exposure respiratory tract irritation | 3, H 335        | experience at humans      |

**Hazard statements**

**H 318** Causes serious eye damage

**H 315** Causes skin irritation

**H 335** May cause respiratory irritation

**2.1.2 Other information**

Full text of the H phrases, hazard statements and EU risk phrases in section 16  
Bodenbinder dust may cause irritation of the respiratory system.

# Bodenbinder

## according to Regulation (EC) No 1907/2006 (REACH)

2022/12/21 Version 6.2

Replaces all previous versions

Print date: 2022/12/21

When Bodenbinder reacts with water, for instance when making concrete or mortar, or when the Bodenbinder becomes damp, a strong alkaline solution is produced. Due to the high alkalinity, wet Bodenbinder may provoke skin and eye irritation.

### 2.2. Label elements

#### 2.2.1 According to Regulation (EC) No 1272/2008

##### Hazard pictograms



##### Signal word

Danger

##### Hazard statements

H 318 Causes serious eye damage

H 315 Causes skin irritation

H 335 May cause respiratory irritation

##### Precautionary statements

P 280 Wear protective gloves/protective clothing/eye protection/face protection

P 305 + P 351 + P 338 + P 310: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician

P 302 + P 352 + P 333 + P 313: IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention

P 261 + P 304 + P 340 + P 312: Avoid breathing dust/fume/gas/mist/vapours/spray. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

P 102 Keep out of reach of children

P 501 Dispose of contents/container to in accordance with local/regional/national/international regulations (to be specified)

##### Supplemental information

Skin contact with wet Bodenbinder may cause irritation, dermatitis or burns.

May cause damage to products made of aluminium or other non-noble metals.

### 2.3. Other hazards

Cement does not meet the criteria for PBT or vPvB in accordance with Annex XIII of REACH (Regulation (EC) No 1907/2006).

The product contains chromate, whereby the content of water-soluble chromium (VI) is less than 0.0002%. (determined according to EN 196-10). At not proper storage (access of moisture) or superposition the chromate reducing agent may lose its effectiveness and it can not be excluded a sensitizing effect of the cement in contact with skin. (H 317 or EUH203)

Remains low-chromate for bulk goods at least 2 months after the date of delivery and as bagged goods for at least 6 months from the production date if stored properly in dry conditions.

## SECTION 3: Composition/information on ingredients

### 3.1 Substance




Not applicable, since the product is a mixture

### 3.2 Mixtures

Mixtures containing cement types according to the EN 197-1 standard and Quicklime according to EN 459-1.

#### Hazardous substances

| Name                        | Portland cement clinker <sup>(1)</sup> | Flue dust <sup>(2)</sup> from production of cement clinker | Quicklime             |
|-----------------------------|--|--|-----------------------|
| EC number                   | 266-043-4                              | 270-659-9  | 215-138-9             |
| CAS number                  | 65997-15-1                             | 68475-76-3   | 1305-78-8             |
| Registration number         | exempted (see 15.1)                    | 01-2119486767-17-xxxx                                      | 01-2119475325-36-xxxx |
| Concentration range [wt.-%] | 5 - 100                                | 0 - 5  | 0 - 60                |
| SLC/M-Faktor/ATE            | Not applicable                         | Not applicable   | Not applicable        |

| Classification acc. to European Regulation<br>(EC) No 1272/2008 | Danger, Cat. 1  |               | Danger, Cat. 1   |               | Danger, Cat. 1  |               |
|---|---|---------------|--|---------------|---|---------------|
|   |   | Skin irrit. 2 | H 315  | Skin irrit. 2 | H 315   | Skin irrit. 2 |
|   | Skin Sens. 1B   | H 317         | Skin Sens. 1B  | H 317         | Skin Sens. 1B   | H 317         |
|   | Eye Dam. 1  | H 318         | Eye Dam. 1   | H 318         | Eye Dam. 1  | H 318         |
|   | STOT SE. 3  | H 335         | STOT SE. 3   | H 335         | STOT SE. 3  | H 335         |
|   |  |               |  |               |  |               |

(1) Cement is a mixture according to REACH and is not subject to registration. Cement clinker is exempt from registration (Art 2.7 (b) and Annex V.10 of REACH).

(2) Flue Dust is a substance (UVCB), is generated by the production of cement clinker; Another common name is cement kiln dust and bypass flour, dust filter, EGR dust and clinker dust.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General notes

No personal protective equipment is needed for first aid responders. First aid workers should avoid contact with wet Bodenbinder or wet Bodenbinder containing preparations.

#### Following contact with eyes

Do not rub eyes in order to avoid possible cornea damage as a result of mechanical stress.

Remove contact lenses if any. Incline head to injured eye, open the eyelid(s) widely and flush eye(s) immediately by thoroughly rinsing with plenty of clean water for at least 20 minutes to remove all particles. Avoid flushing particles into uninjured eye. If possible, use isotonic water (0.9 % NaCl). Contact a specialist of occupational medicine or an eye specialist.

#### Following skin contact

For dry Bodenbinder, remove and rinse abundantly with water.

For wet Bodenbinder, wash skin with plenty of water.

Remove contaminated clothing, footwear, watches, etc. and clean thoroughly before re-using them.

Seek medical treatment in all cases of irritation or burns.

#### Following inhalation

Move the person to fresh air. Dust in throat and nasal passages should clear spontaneously. Contact a physician if irritation persists or later develops or if discomfort, coughing or other symptoms persist.

#### Following ingestion

Do not induce vomiting. If the person is conscious, wash out mouth with water and give plenty of water to drink. Get immediate medical attention or contact the anti poison centre.

### 4.2. Most important symptoms and effects, both acute and delayed

**Eyes:** Eye contact with Bodenbinder (dry or wet) may cause serious and potentially irreversible injuries.

**Skin:** Bodenbinder may have an irritating effect on moist skin (due to sweat or humidity) after prolonged contact or may cause contact dermatitis after repeated contact.

Prolonged skin contact with wet Bodenbinder or wet concrete may cause serious burns because they develop without pain being felt (for example when kneeling in wet concrete even when wearing trousers).

For more details see Reference (1).

**Inhalation:** Repeated inhalation of dust of common Bodenbinders over a long period of time increases the risk of developing lung diseases.

**Environment:** Under normal use, common Bodenbinder is not hazardous to the environment.

### 4.3. Indication of any immediate medical attention and special treatment needed

When contacting a physician, take this SDS with you.

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

Common Bodenbinders are not flammable.

**5.2. Special hazards arising from the substance or mixture**

Bodenbinders are non-combustible and non-explosive and will not facilitate or sustain the combustion of other materials.

**5.3. Advice for fire-fighters**

Bodenbinder poses no fire-related hazards. No need for special protective equipment for fire fighters.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****6.1.1 For non-emergency personnel**

Wear protective equipment as described under section 8 and follow the advice for safe handling and use given under section 7.

**6.1.2 For emergency responders**

Emergency procedures are not required.

However, respiratory protection is needed in situations with high dust levels.

**6.2. Environmental precautions**

Do not wash Bodenbinder down sewage and drainage systems or into bodies of water (e.g. streams).

**6.3. Methods and material for containment and cleaning up**

Collect the spillage in a dry state if possible.

**Dry Bodenbinder**

Use cleanup methods such as vacuum clean-up or vacuum extraction (Industrial portable units, equipped with high efficiency particulate air filters (EPA and HEPA filters, EN 1822-1:2009) or equivalent technique) which do not cause airborne dispersion. Never use compressed air. Alternatively, wipe-up the dust by mopping, wet brushing or by using water sprays or hoses (fine mist to avoid that the dust becomes airborne) and remove slurry. If not possible, remove by slurring with water (see wet Bodenbinder).

When wet cleaning or vacuum cleaning is not possible and only dry cleaning with brushes can be done, ensure that the workers wear the appropriate personal protective equipment and prevent dust from spreading. Avoid inhalation of Bodenbinder and contact with skin. Place spilled materials into a container. Solidify before disposal as described under section 13.

**Wet Bodenbinder**

Clean up wet Bodenbinder and place in a container. Allow material to dry and solidify before disposal as described under section 13.

**6.4. Reference to other sections**

See sections 8 and 13 for more details.

**SECTION 7: Handling and storage**

Do not handle or store near food and beverages or smoking materials.

**7.1. Precautions for safe handling****7.1.1 Protective measures**

Follow the recommendations as given under section 8. To clean up dry Bodenbinder, see subsection 6.3.

**Measures to prevent fire**

Not applicable.

**Measures to prevent aerosol and dust generation**

Do not sweep. Use dry cleanup methods such as vacuum clean-up or vacuum extraction, which do not cause airborne dispersion. Further information on dust prevention can be found at the DGUV: <https://www.dguv.de/staub-info/zehn-goldene-regeln/index.jsp> and on the NePSi platform: <http://www.nepsi.eu/agreement-good-practice-guide/good-practice-guide.aspx>.

**Measure to protect the environment**

No particular measures.

**7.1.2 Information on general occupational hygiene**

Do not handle or store near food and beverages or smoking materials. In dusty environment, wear dust mask and protective goggles. Use protective gloves to avoid skin contact.

**7.2. Conditions for safe storage, including any incompatibilities**

Bulk Bodenbinder should be stored in silos that are waterproof, dry (i.e. with internal condensation minimised), clean and protected from contamination.

# Bodenbinder

## according to Regulation (EC) No 1907/2006 (REACH)

2022/12/21 Version 6.2

Replaces all previous versions

Print date: 2022/12/21

Engulfment hazard: To prevent engulfment or suffocation, do not enter a confined space, such as a silo, bin, bulk truck, or other storage container or vessel that stores or contains Bodenbinder without taking the proper security measures. Bodenbinder can build-up or adhere to the walls of a confined space. The Bodenbinder can release, collapse or fall unexpectedly.

Packed products should be stored in unopened bags clear of the ground in cool, dry conditions and protected from excessive draught in order to avoid degradation of quality. Bags should be stacked in a stable manner.

Do not use aluminium containers due to incompatibility of the materials.

For Bodenbinder treated with a Cr (VI) reducing agent according to the regulations given in section 15, the effectiveness of the reducing agent diminishes with time. Therefore, Bodenbinder bags and/or delivery documents will contain information on the packaging date, the storage conditions and the storage period appropriate to maintaining the activity of the reducing agent and to keeping the content of soluble chromium (VI) below 0.0002 % of the total dry weight of the Bodenbinder ready for use, according to EN 196-10. They will also indicate the appropriate storage conditions for maintaining the effectiveness of the reducing agent.

### 7.3. Specific end use(s)

No additional information for the specific end uses (see section 1.2).

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

| CAS-Nr.   | type of assesment value                             | assesment value                                     | Short-term exposure limit (15 min reference period) | source                        | Comment     |
|---|---|---|---|-------------------------------|-------------|
| <b>general dust limit value (portland cement)</b> |   |   |   |                               |             |
| 65997-15-1  | Long-term exposure Limit (8 h TWA reference period) | 4 mg/m <sup>3</sup> (A)<br>10 mg/m <sup>3</sup> (E) | not fixed   | HES EH 40–2011 <sup>(2)</sup> |             |
| <b>water-soluble chromium (VI)</b>                |   |   |   |                               |             |
|   | limit   | 2 ppm in Zement                                     | not fixed   | Regulation (EG) Nr. 1907/2006 | EN 196 - 10 |
| <b>Quarz fine dust *</b>                          |   |   |   |                               |             |
|   | Assesment standard                                  | 0,05 mg/m <sup>3</sup> (A)                          | Excess factor 8                                     | TRGS 559                      | -           |

A = respirable fraction; E = Inhalable fraction \* must be taken into account if the quartz content is higher than 4 %, as compliance with the general dust limit value is then no longer sufficient.

Information on the Technical Rules for Hazardous Substances (TRGS) in (2)

### 8.2. Exposure controls

#### 8.2.1 Appropriate engineering controls

Measures to reduce generation of dust and to avoid dust propagating in the environment such as dedusting, exhaust ventilation and dry clean-up methods which do not cause airborne dispersion.

If no appropriate exposure data are available, exposure estimation can be done by using MEASE [Reference (3)]. Technical control measures (table in 8.2.1) and individual protection measures (table in 8.2.2) are recommended for all identified uses (section 1.2).

For each individual PROC\*, companies can choose from either option A) or B) in the two tables, according to what is best suited to their specific situation. If one option is chosen, then the same option (A and A or B and B) has to be chosen from the other table.

| Exposure Scenario  | PROC*                   | Exposure  | Localised controls  | Efficiency  |
|--|-------------------------|---|---|---|
| Industrial manufacture/formulation of hydraulic building and construction materials    | 2, 3                    | Duration is not restricted (up to 480 minutes per shift, 5 shifts a week) | not required  | -   |
|  | 14, 26                  |   | A) not required or<br>B) generic local exhaust ventilation    | -<br>78 %   |
|  |                         |   | 5, 8b, 9  | A) general ventilation or<br>B) generic local exhaust ventilation |
| Industrial uses of dry hydraulic building and construction materials (indoor, outdoor) | 2                       |   | not required  | -   |
|  | 14, 22, 26              |   | A) not required or<br>B) generic local exhaust ventilation    | -<br>78 %   |
|  |                         |   | 5, 8b, 9  | A) general ventilation or<br>B) generic local exhaust ventilation |
| Industrial uses of wet suspension of hydraulic building and construction materials     | 7                       |   | A) not required or<br>B) integrated local exhaust ventilation | -<br>87 %   |
|  | 2, 5, 8b, 9, 10, 13, 14 |   | not required  | -   |
|  | 2                       |   | not required  | -   |

| Exposure Scenario  | PROC*                           | Exposure | Localised controls  | Efficiency |
|--|---------------------------------|----------|---|------------|
| Professional use of dry hydraulic building and construction material (indoor, outdoor) | 9, 26                           |          | A) not required or<br>B) generic local exhaust ventilation                              | -<br>72 %  |
|  | 5, 8a, 8b, 14                   |          | A) not required or<br>B) generic local exhaust ventilation                              | -<br>77 %  |
|  | 19                              |          | localised controls are not applicable, process only in good ventilated rooms or outdoor | 50 %       |
| Professional uses of wet suspensions of hydraulic building and construction materials  | 11                              |          | A) not required or<br>B) integrated local exhaust ventilation                           | -<br>72 %  |
|  | 2, 5, 8a, 8b, 9, 10, 13, 14, 19 |          | not required  | -          |

\* PROC's are identified uses and defined in section 16

**8.2.2 Individual protection measures such as personal protection equipment**

**General:** During work avoid kneeling in fresh Bodenbinder wherever possible. If kneeling is absolutely necessary then appropriate waterproof personal protective equipment must be worn.

Do not eat, drink or smoke when working with Bodenbinder to avoid contact with skin or mouth.

Before starting to work with Bodenbinder, apply a barrier creme and reapply it at regular intervals.

Immediately after working with Bodenbinder or Bodenbinder-containing materials, workers should wash or shower or use skin moisturisers.

Remove contaminated clothing, footwear, watches, etc. and clean thoroughly before re-using them.

**Eye/face protection**



Wear approved glasses or safety goggles according to EN 166 when handling dry or wet Bodenbinder to prevent contact with eyes.

**Skin protection**



Use impervious, abrasion and made of low soluble Cr (VI) containing material. Use watertight wear, and alkali resistant protective gloves (e.g. nitrile soaked cotton gloves with CE marking) internally lined with cotton, boots, closed long-sleeved protective clothing as well as skin care products (e.g. barrier creams) to protect the skin from prolonged contact with wet cement. Particular care should be taken to ensure that wet Bodenbinder does not enter the boots. Regarding gloves, investigations have proven that nitrile impregnated cotton gloves (layer thickness of c. 0.15 mm) provide sufficient protection over a period of 480 minutes, subject to normal wear and tear which can be task dependent. Always change damaged or soaked gloves immediately. Always have spare gloves in ready supply.

**Respiratory protection**



When a person is potentially exposed to dust levels above exposure limits, use appropriate respiratory protection. The type of respiratory protection should be adapted to the dust level and conform to the relevant EN standard, (e.g. EN 149, EN 140, EN 14387, EN 1827) or national standard.

**Thermal hazards**

Not applicable.

| Exposure Scenario  | PROC*                   | Exposure  | Specification of respiratory protective equipment (RPE) | RPE efficiency -assigned protection factor (APF) |
|--|-------------------------|---|---|--|
| Industrial manufacture/formulation of hydraulic building and construction materials    | 2, 3                    | Duration is not restricted (up to 480 minutes per shift, 5 shifts a week) | not required  | -  |
|  | 14, 26                  |   | A) P1 mask (FF, FM) or<br>B) not required               | APF = 4<br>-                                     |
|  | 5, 8b, 9                |   | A) P2 mask (FF, FM) or<br>B) P1 mask (FF, FM)           | APF = 10<br>APF = 4                              |
| Industrial uses of dry hydraulic building and construction materials (indoor, outdoor) | 2                       |   | not required  | -  |
|  | 14, 22, 26              |   | A) P1 mask (FF, FM) or<br>B) not required               | APF = 4<br>-                                     |
|  | 5, 8b, 9                |   | A) P2 mask (FF, FM) or<br>B) P1 mask (FF, FM)           | APF = 10<br>APF = 4                              |
|  | 2, 5, 8b, 9, 10, 13, 14 | A) P1 mask (FF, FM) or<br>B) not required                                 | APF = 10<br>-   |  |



| Exposure Scenario  | PROC*                                 | Exposure | Specification of respiratory protective equipment (RPE) | RPE efficiency -assigned protection factor (APF) |
|--|---------------------------------------|----------|---|--|
| Industrial uses of wet suspension of hydraulic building and construction materials     | 7                                     |          | not required  | -  |
| Professional use of dry hydraulic building and construction material (indoor, outdoor) | 2                                     |          | P1 mask (FF, FM)  | APF = 4  |
|  | 9, 26                                 |          | A) P2 mask (FF, FM) or<br>B) P1 mask (FF, FM)           | APF = 10<br>APF = 4                              |
|  | 5, 8a, 8b, 14                         |          | A) P3 mask (FF, FM) or<br>B) P1 mask (FF, FM)           | APF = 20<br>APF = 4                              |
|  | 19                                    |          | P2 mask (FF, FM)  | APF = 10   |
| Professional uses of wet suspensions of hydraulic building and construction materials  | 11                                    |          | A) P2 mask (FF, FM) or<br>B) P1 mask (FF, FM)           | APF = 10<br>-                                    |
|  | 2, 5, 8a, 8b,<br>9, 10, 13, 14,<br>19 |          | not required  | -  |

\* PROC's are identified uses and defined in section 16

An overview of the APFs of different RPE (according to EN 529:2005) can be found in the glossary of MEASE [Reference (3)].

Any RPE as defined above shall only be worn if the following principles are implemented in parallel: The duration of work (compare with "duration of exposure" above) should reflect the additional physiological stress for the worker due to the breathing resistance and mass of the RPE itself, due to the increased thermal stress by enclosing the head. In addition, it shall be considered that the worker's capability of using tools and of communicating are reduced during the wearing of RPE.

For reasons as given above, the worker should therefore be (i) healthy (especially in view of medical problems that may affect the use of RPE), (ii) have suitable facial characteristics reducing leakages between face and mask (in view of scars and facial hair). The recommended devices above which rely on a tight face seal will not provide the required protection unless they fit the contours of the face properly and securely.

The employer and self-employed persons have legal responsibilities for the maintenance and issue of respiratory protective devices and the management of their correct use in the workplace. Therefore, they should define and document a suitable policy for a respiratory protective device programme including training of the workers.

### 8.2.3 Environmental exposure controls

Environmental exposure control for the emission of Bodenbinder particles into air has to be in accordance with the available technology and regulations for the emission of general dust particles.

Environmental exposure control is relevant for the aquatic environment as emissions of Bodenbinder in the different life-cycle stages (production and use) mainly apply to ground and waste water. The aquatic effect and risk assessment cover the effect on organisms/ecosystems due to possible pH changes related to hydroxide discharges. The toxicity of other dissolved inorganic ions is expected to be negligible compared to the potential pH effect.

Any effects that might occur during production and use would be expected to take place on a local scale. The pH of effluent and surface water should not exceed 9. Otherwise it could have an impact on municipal sewage treatment plants (STPs) and industrial waste water treatment plants (WWTPs). For that assessment of the exposure, a stepwise approach is recommended:

- Tier 1:** Retrieve information on effluent pH and the contribution of the Bodenbinder on the resulting pH. Should the pH be above 9 and be predominantly attributable to Bodenbinder, then further actions are required to demonstrate safe use.
- Tier 2:** Retrieve information on receiving water pH after the discharge point. The pH of the receiving water shall not exceed the value of 9.
- Tier 3:** Measure the pH in the receiving water after the discharge point. If pH is below 9, safe use is reasonably demonstrated. If pH is found to be above 9, risk management measures have to be implemented: the effluent has to undergo neutralisation, thus ensuring safe use of Bodenbinder during production or use phase.

No special emission control measures are necessary for the exposure to the terrestrial environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

This information applies to the whole mixture.

- (a) Physical state: Dry cement is a finely ground solid inorganic material.
- (b) Color : grey or white powder
- (c) Odor: Odorless
- (d) Melting point: > 1250 °C
- (e) Boiling point or initial boiling point and boiling range: Not applicable, as under normal atmospheric conditions the melting point > 1250 °C.

# Bodenbinder

## according to Regulation (EC) No 1907/2006 (REACH)

2022/12/21 Version 6.2

Replaces all previous versions

Print date: 2022/12/21

- (f) Flammability: Not applicable, as material is not combustible.
- (g) Upper/Lower explosion limit: Do not apply to solids.
- (h) Flash point: Not applicable as is not a liquid
- (i) Auto-ignition temperature: Not applicable, only applies to gases and liquids.
- (j) Decomposition temperature: Not applicable, as not self-reactive and no organic peroxides present.
- (k) pH-value (T = 20 °C in water, water-solid ratio 1:2): 11-13.5
- (l) Kinematic viscosity: Not applicable, as not a liquid.
- (m) Solubility: in water (T = 20 °C): low (0.1-1.5 g/l)
- (n) Partition coefficient n-octanol/water (log value): Not applicable, as it is an inorganic mixture.
- (o) Vapor pressure: Not applicable, as melting point > 1250 °C.
- (p) Density and/or relative density: 2.75-3.20 g/cm<sup>3</sup>; bulk density: 0.9-1.5 g/cm<sup>3</sup>
- (q) Relative vapor density: Not applicable, only applies to gases and liquids.
- (r) Particle characteristics: Typical average particle size: 5-30 µm

### 9.2. Other information

#### 9.2.1 Information on physical hazard classes

Not applicable

#### 9.2.2 Other safety characteristics

Not applicable.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

When mixed with water, Bodenbinder will harden into a stable mass that is not reactive in normal environments.

### 10.2. Chemical stability

Dry Bodenbinder are stable as long as they are properly stored (see section 7) and compatible with most other building materials. They should be kept dry.

Contact with incompatible materials should be avoided. Wet Bodenbinder is alkaline and incompatible with acids, with ammonium salts, with aluminium or other non-noble metals. Bodenbinder dissolves in hydrofluoric acid to produce corrosive silicon tetrafluoride gas. Bodenbinder reacts with water to form silicates and calcium hydroxide. Silicates in cement react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride. Quicklime is chemically stable, but reacts vigorously with water to form calcium hydroxide, while generating heat. Quicklime also reacts with carbon dioxide to form calcium carbonate.

### 10.3. Possibility of hazardous reactions

Bodenbinder do not cause hazardous reactions.

### 10.4. Conditions to avoid

Due to the potential for vigorous reaction and release of heat as a function of Quicklime concentration the mixing with acids and water should be done in a controlled process. Humid conditions during storage may cause lump formation and loss of product quality.

### 10.5. Incompatible materials

Acids, ammonium salts, aluminium or other non-noble metals. Uncontrolled use of aluminium powder in wet Bodenbinder should be avoided as hydrogen is produced.

### 10.6. Hazardous decomposition products

Bodenbinder will not decompose into any hazardous products. Addition of water to Quicklime has generated temperatures as high as 80°C.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

| Hazard class                  | Cat. | Effect   | Reference               |
|-------------------------------|------|--|-------------------------|
| Acute toxicity – dermal       | -    | Limit test, rabbit, 24 hours contact, 2,000 mg/kg body weight – no lethality.<br>Based on available data, the classification criteria are not met.                 | (4)                     |
| Acute toxicity-<br>inhalation | -    | No acute toxicity by inhalation observed.<br>Based on available data, the classification criteria are not met.   | (10)                    |
| Acute toxicity – oral         | -    | No indication of oral toxicity from studies with cement kiln dust.<br>Based on available data, the classification criteria are not met.                            | Literature survey       |
| Skin corrosion/<br>irritation | 2    | Cement in contact with wet skin may cause thickening, cracking or fissuring of the skin.<br>Prolonged contact in combination with abrasion may cause severe burns. | (4)<br>Human experience |



| Hazard class                  | Cat. | Effect  | Reference                         |
|-------------------------------|------|---|-----------------------------------|
| Serious eye damage/irritation | 1    | Portland cement clinker caused a mixed picture of corneal effects and the calculated irritation index was 128.<br>Common cements contain varying quantities of Portland cement clinker, fly ash, blast furnace slag, gypsum, natural pozzolans, burnt shale, silica fume and limestone.<br>Direct contact with cement may cause corneal damage by mechanical stress, immediate or delayed irritation or inflammation. Direct contact by larger amounts of dry cement or splashes of wet cement may cause effects ranging from moderate eye irritation (e.g. conjunctivitis or blepharitis) to chemical burns and blindness.   | (11), (12)                        |
| Skin sensitisation            | 1B   | Some individuals may develop eczema upon exposure to wet cement dust, caused either by the high pH which induces irritant contact dermatitis after prolonged contact, or by an immunological reaction to soluble Cr (VI) which elicits allergic contact dermatitis.<br>The response may appear in a variety of forms ranging from a mild rash to severe dermatitis and is a combination of the two above mentioned mechanisms.<br>If the cement contains a soluble Cr (VI) reducing agent and as long as the mentioned period of effectiveness of the chromate reduction is not exceeded, a sensitising effect is not expected [Reference (5)].                         | (5), (13), (17), (18)             |
| Respiratory sensitisation     | -    | There is no indication of sensitisation of the respiratory system.<br>Based on available data, the classification criteria are not met.   | (1)                               |
| Germ cell mutagenicity        | -    | No indication.<br>Based on available data, the classification criteria are not met.   | (14), (15)                        |
| Carcinogenicity               | -    | No causal association has been established between Portland cement exposure and cancer.<br>The epidemiological literature does not support the designation of Portland cement as a suspected human carcinogen<br>Portland cement is not classifiable as a human carcinogen (According to ACGIH A4: Agents that cause concern that they could be carcinogenic for humans but which cannot be assessed conclusively because of a lack of data. In vitro or animal studies do not provide indications of carcinogenicity that are sufficient to classify the agent with one of the other notations.).<br>Based on available data, the classification criteria are not met. | (1)<br>(16)                       |
| Reproductive toxicity         | -    | Based on available data, the classification criteria are not met.   | No evidence from human experience |
| STOT-single exposure          | 3    | Cement dust may irritate the throat and respiratory tract. Coughing, sneezing, and shortness of breath may occur following exposures in excess of occupational exposure limits.<br>Overall, the pattern of evidence clearly indicates that occupational exposure to cement dust has produced deficits in respiratory function. However, evidence available at the present time is insufficient to establish with any confidence the dose-response relationship for these effects.   | (1)                               |
| STOT-repeated exposure        | -    | There is an indication of COPD. The effects are acute and due to high exposures. No chronic effects or effects at low concentration have been observed.<br>Based on available data, the classification criteria are not met.  | (17)                              |
| Aspiration hazard             | -    | Not applicable as cements are not used as an aerosol.   |                                   |

Apart from skin sensitisation, Portland cement clinker and common cements have the same toxicological and eco-toxicological properties.

### Medical conditions aggravated by exposure

Inhaling cement dust may aggravate existing respiratory system disease(s) and/or medical conditions such as emphysema or asthma and/or existing skin and/or eye conditions.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

Not applicable

### 11.2.2. other information

Not applicable

## SECTION 12: Ecological information

### 12.1. Toxicity

The product is not hazardous to the environment. Ecotoxicological tests with Portland cement on *Daphnia magna* (U.S. EPA, 1994a) [Reference (6)] and *Selenastrum coli* (U.S. EPA, 1993) [Reference (7)] have shown little toxicological impact. Therefore LC 50 and

EC 50 values could not be determined [Reference (8)]. There is no indication of sediment phase toxicity [Reference (9)]. The addition of large amounts of Bodenbinder to water may, however, cause a rise in pH and may, therefore, be toxic to aquatic life under certain circumstances.

**12.2. Persistence and degradability**

Not applicable as Bodenbinder is an inorganic material. After hardening, Bodenbinder presents no toxicity risks.

**12.3. Bioaccumulative potential**

Not applicable as Bodenbinder is an inorganic material. After hardening, Bodenbinder presents no toxicity risks.

**12.4. Mobility in soil**

Not applicable as Bodenbinder is an inorganic material. After hardening, Bodenbinder presents no toxicity risks.

**12.5. Results of PBT and vPvB assessment**

Not applicable as Bodenbinder is an inorganic material. After hardening, Bodenbinder presents no toxicity risks.

**12.6. Endocrine disrupting properties**

Not applicable

**12.7. Other adverse effects**

Not applicable.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods**

Do not dispose of into sewage systems or surface waters.

**Product - Bodenbinder that has exceeded its shelf life**

(and when demonstrated that it contains more than 0.0002 % soluble Cr (VI)): shall not be used/sold other than for use in controlled closed and totally automated processes or should be recycled or disposed of according to local legislation or treated again with a reducing agent.

**Product - unused residue or dry spillage**

Pick up dry unused residue or dry spillage as is. Mark the containers. Possibly reuse depending upon shelf life considerations and the requirement to avoid dust exposure. In case of disposal, harden with water and dispose according to "Product – after addition of water, hardened"

**Product – slurries**

Allow to harden, avoid entry in sewage and drainage systems or into bodies of water (e.g. streams) and dispose of as explained below under "Product - after addition of water, hardened".

**Product - after addition of water, hardened**

Dispose of according to the local legislation. Avoid entry into the sewage water system. Dispose of the hardened product as concrete waste. Due to the inertisation, concrete waste is not a dangerous waste.

**EWC entries:** 10 13 14 (waste from manufacturing of cement – waste concrete or concrete sludge) or 17 01 01 (construction and demolition wastes - concrete).

**Packaging**

Completely empty the packaging and process it according to local legislation.

**EWC entry:** 15 01 01 (waste paper and cardboard packaging).

**SECTION 14: Transport information**

Bodenbinder is not covered by the international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID), therefore no classification is required.

No special precautions are needed apart from those mentioned under section 8.

**14.1. UN number or ID number**

Not applicable.

**14.2. UN proper shipping name**

Not applicable.

**14.3. Transport hazard class(es)**

Not applicable.

**14.4. Packing group**

Not applicable.

**14.5. Environmental hazards**

Not applicable.

**14.6. Special precautions for user**

Not applicable.

**14.7. Maritime transport in bulk according to IMO instruments**

Not applicable.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Bodenbinder is a mixture according to REACH and is not subject to registration. Cement clinker is exempt from registration (Art 2.7 (b) and Annex V.10 of REACH).

The marketing and use of Bodenbinder is subject to a restriction on the content of soluble Cr (VI) (REACH Annex XVII point 47 Chromium (VI) compounds):

1. Bodenbinder and cement-containing mixtures shall not be placed on the market, or used, if they contain, when hydrated, more than 2 mg/kg (0.0002 %) soluble chromium (VI) of the total dry weight of the cement.
2. If reducing agents are used, then without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of cement or cement-containing mixtures is visibly, legibly and indelibly marked with information on the packing date, as well as on the storage conditions and the storage period appropriate to maintaining the activity of the reducing agent and to keeping the content of soluble chromium (VI) below the limit indicated in paragraph 1.
3. By way of derogation, paragraphs 1 and 2 shall not apply to the placing on the market for, and use in, controlled closed and totally automated processes in which cement and cement-containing mixtures are handled solely by machines and in which there is no possibility of contact with the skin.
4. The Standard for the examination of the content of water-soluble chromium VI of cement and cement-containing mixtures is approved by the European Committee for Standardization (CEN) as the standard method for documentation compliance with the requirements of the section 1.

The so-called "Good practice guides" which contain advice on safe handling practices can be found from: <http://www.nepsi.eu/good-practice-guide.aspx>. These good practices have been adopted under the Social Dialogue "Agreement on Workers' Health Protection through the Good Handling and Use of Crystalline Silica and Products Containing it by Employee and Employer European sectoral associations, among which CEMBUREAU.

**UK national legislation/requirements**

CONIAC Health Hazard Information Sheet No. 26 (CEMENT)

Health and Safety at Work etc Act 1974

Control of Substances Hazardous to Health (Regulations)

PORTLAND CEMENT DUST – criteria document for an occupational exposure limit. June 1994 (ISBN 07176–0763–1)

HSE Guidance Notes EH 26 (Occupational Skin Diseases – Health and Safety Precautions)

HSE Guidance Note EH 40 (Workplace Exposure Limits)

Any authorised manual on First Aid by St. John's/St. Andrew's/Red Cross

Manual Handling Operations Regulations

Environmental Protection Act

**15.2. Chemical Safety Assessment**

No chemical safety assessment has been carried out.

**SECTION 16: Other information****16.1 Indication of changes**

compared to the last version, UFI's and new products and product names have been introduced under point 1.1. This version 6.2 complies with the requirements for the compilation of the safety data sheet according to Regulation (EU) 2020/878 of 18 June 2020.

**16.2 Abbreviations and acronyms**

|         |   |
|---------|---|
| ACGIH   | American Conference of Industrial Hygienists                            |
| ADR/RID | European Agreements on the transport of Dangerous goods by Road/Railway |
| APF     | Assigned Protection Factor  |
| CAS     | Chemical Abstracts Service  |
| CLP     | Classification, Labelling and Packaging (Regulation (EC) No 1272/2008)  |
| COPD    | Chronic Obstructive Pulmonary Disease                                   |

|           |  |
|-----------|--|
| DNEL      | Derived No-Effect Level  |
| EC 50     | Half maximal Effective Concentration   |
| ECHA      | European CHemicals Agency  |
| EINECS    | European INventory of Existing Commercial chemical Substances  |
| EPA       | Efficiency Particulate Air filter  |
| ES        | Exposure Scenario  |
| EWC       | European Waste Catalogue   |
| FF P      | Filtering Facepiece against Particles (disposable)   |
| FM P      | Filtering Mask against Particles with filter cartridge   |
| GefStoffV | Gefahrstoffverordnung  |
| HEPA      | High Efficiency Particulate Air filter   |
| H&S       | Health and Safety  |
| IATA      | International Air Transport Association  |
| IMDG      | International agreement on the Maritime transport of Dangerous Goods   |
| LC 50     | Median lethal dose   |
| MEASE     | Metals Estimation and Assessment of Substance Exposure, EBRC Consulting GmbH for Eurometaux, <a href="http://www.ebrc.de/ebrc/ebrc-mease.php">http://www.ebrc.de/ebrc/ebrc-mease.php</a> |
| MS        | Member State   |
| OELV      | Occupational Exposure Limit Value  |
| PBT       | Persistent, Bio-accumulative and Toxic   |
| PNEC      | Predicted No-Effect Concentration  |
| PROC      | PROcess Category   |
| RE        | Repeated Exposure  |
| REACH     | Registration, Evaluation and Authorisation of Chemicals  |
| RPE       | Respiratory Protective Equipment   |
| SCOEL     | Scientific Committee on Occupational Exposure Limit values   |
| SDS       | Safety Data Sheet  |
| SE        | Single Exposure  |
| STP       | Sewage Treatment Plant   |
| STOT      | Specific Target Organ Toxicity   |
| TLV-TWA   | Threshold Limit Value-Time-Weighted Average  |
| TRGS      | Technische Regeln für GefahrStoffe   |
| VLE-MP    | Exposure limit value-weighted average in mg by cubic meter of air  |
| vPvB      | Very Persistent, very Bio-accumulative   |
| w/w       | Weight by weight   |
| WWTP      | Waste Water Treatment Plant  |

**16.3 Process category and descriptors**

For the professional user, the process categories and descriptors according to ECHA guidance R.12 (ECHA-2010-G-05) can be assigned to (s. Table)

| PROC | Identified Uses - Use Description   | Manufacture/ Formulation of         | Professional/<br>Industrial use of |
|------|---|-------------------------------------|------------------------------------|
|      |   | building and construction materials |                                    |
| 2    | Use in closed, continuous process with occasional controlled exposure                             | X                                   | X                                  |
| 3    | Use in closed batch process   | X                                   | X                                  |
| 5    | Mixing or blending in batch process for formulation of preparations and articles                  | X                                   | X                                  |
| 7    | Industrial spraying   |                                     | X                                  |
| 8a   | Transfer of substance or preparation from/to vessels/large containers at non-dedicated facilities |                                     | X                                  |
| 8b   | Transfer of substance or preparation from/to vessels/large containers a dedicated facilities      | X                                   | X                                  |
| 9    | Transfer of substance or preparation into small containers  | X                                   | X                                  |
| 10   | Roller application or brushing  |                                     | X                                  |
| 11   | Non-Industrial spraying   |                                     | X                                  |
| 13   | Treatment of articles by dipping and pouring  |                                     | X                                  |

| PROC | Identified Uses - Use Description  | Manufacture/ Formulation of         | Professional/<br>Industrial use of |
|------|--|-------------------------------------|------------------------------------|
|      |  | building and construction materials |                                    |
| 14   | Production of preparations or articles by tableting, compression extrusion, pelletisation                | X                                   | X                                  |
| 19   | Hand-mixing with intimate contact and only PPE available   |                                     | X                                  |
| 22   | Potentially closed processing operations with minerals/metals at elevated temperature Industrial setting |                                     | X                                  |
| 26   | Handling of solid inorganic substances at ambient temperature  | X                                   | X                                  |

**16.4 Relevant H-statements (number and full text):**

- H 315** Causes skin irritation  
**H 317** May cause an allergic skin reaction  
**H 318** Causes serious eye damage  
**H 335** May cause respiratory irritation  
**EUH 203** Contains chromium (VI). May cause allergic reactions.

**16.5 Key literature references and sources of data**

- (1) Portland Cement Dust - Hazard assessment document EH75/7, UK Health and Safety Executive, 2006: <http://www.hse.gov.uk/pubns/web/portlandcement.pdf>.
- (2) EH 40/2005 Workplace exposure limits; HSE-Books, second edition 2011 (ISBN 978 0 7176 6446 7)
- (3) MEASE 1.02.01 Exposure assessment tool for metals and inorganic substances, EBRC Consulting GmbH für Eurometaux, 2010: <http://www.ebrc.de/tools/mease.php>.
- (4) Observations on the effects of skin irritation caused by cement, Kietzman et al, Dermatosen, 47, 5, 184-189 (1999).
- (5) Epidemiological assessment of the occurrence of allergic dermatitis in workers in the construction industry related to the content of Cr (VI) in cement, NIOH, Page 11, 2003.
- (6) U.S. EPA, Short-term Methods for Estimating the Chronic Toxicity of Effluents and Receiving Waters to Freshwater Organisms, 3rd ed. EPA/600/7-91/002, Environmental Monitoring and Support Laboratory, U.S. EPA, Cincinnati, OH (1994a) and 4th ed. EPA-821-R-02-013, US EPA, office of water, Washington D.C. (2002).
- (7) U.S. EPA, Methods for Measuring the Acute Toxicity of Effluents and Receiving Waters to Freshwater and Marine Organisms, 4th ed. EPA/600/4-90/027F, Environmental Monitoring and Support Laboratory, U.S. EPA, Cincinnati, OH (1993) and 5th ed. EPA-821-R-02-012, US EPA, office of water, Washington D.C. (2002).
- (8) Environmental Impact of Construction and Repair Materials on Surface and Ground Waters. Summary of Methodology, Laboratory Results, and Model Development. NCHRP report 448, National Academy Press, Washington, D.C., 2001. Final report Sediment Phase Toxicity Test Results with Corophium volutator for Portland clinker prepared for Norcem A.S. by AnalyCen Ecotox AS, 2007.
- (9) Final report Sediment Phase Toxicity Test Results with Corophium volutator for Portland clinker prepared for Norcem A.S. by AnalyCen Ecotox AS, 2007
- (10) TNO report V8801/02, An acute (4-hour) inhalation toxicity study with Portland Cement Clinker CLP/GHS 03-2010 fine in rats, August 2010.
- (11) TNO report V8815/09, Evaluation of eye irritation potential of cement clinker G in vitro using the isolated chicken eye test, April 2010.
- (12) TNO report V8815/10, Evaluation of eye irritation potential of cement clinker W in vitro using the isolated chicken eye test, April 2010.
- (13) European Commission's Scientific Committee on Toxicology, Ecotoxicology and the Environment (SCTEE) opinion of the risks to health from Cr (VI) in cement (Europäische Kommission, 2002): [http://ec.europa.eu/health/archive/ph\\_risk/committees/sct/documents/out158\\_en.pdf](http://ec.europa.eu/health/archive/ph_risk/committees/sct/documents/out158_en.pdf).
- (14) Investigation of the cytotoxic and proinflammatory effects of cement dusts in rat alveolar macrophages, Van Berlo et al, Chem. Res. Toxicol., 2009 Sept; 22(9):1548-58
- (15) Cytotoxicity and genotoxicity of cement dusts in A549 human epithelial lung cells in vitro; Gminski et al, Abstract DGPT conference Mainz, 2008.
- (16) Comments on a recommendation from the American Conference of governmental industrial Hygienists to change the threshold limit value for Portland cement, Patrick A. Hessel and John F. Gamble, EpiLung Consulting, June 2008.

# Bodenbinder

## according to Regulation (EC) No 1907/2006 (REACH)

2022/12/21 Version 6.2

Replaces all previous versions

Print date: 2022/12/21

- (17) Exposure to Thoracic Aerosol in a Prospective Lung Function Study of Cement Production Workers; Noto, H., et al; Ann. Occup. Hyg., 2015, Vol. 59, No. 1, 4–24.
- (18) *Occurrence of allergic contact dermatitis caused by chromium in cement. A review of epidemiological investigations*, Kåre Lenvik, Helge Kjuus, NIOH, Oslo, December 2011.
- (19) ECHA Support Questions and answers agreed with National Helpdesks. ID1695 May 2020.  
<https://echa.europa.eu/es/support/qas-support/qas-agreed-with-national-helpdesks>

### 16.6 Methods in accordance with Article 9 of Regulation (EC) 1272/2008 (CLP) to evaluate the information for classification purposes

The review was conducted in accordance with Article 6, paragraph 5 and Annex I to Regulation (EC) No. 1272/2008.

| Evaluation according to (EC) No. 1272/2008                                  | Hazard category | Classification procedure  |
|---|-----------------|---------------------------|
| Skin irritation   | 2, H 315        | On the basis of test data |
| Serious eye damage/eye irritation   | 1, H 318        | On the basis of test data |
| Specific target organ toxicity single exposure respiratory tract irritation | 3, H 335        | experience at humans      |

### 16.7 Training advice

In addition to health, safety and environmental training programs for their workers, companies must ensure that workers read, understand and apply the requirements of this SDS.

### 16.8 Disclaimer

The information on this data sheet reflects the currently available knowledge and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product, including the use of the product in combination with any other product or any other process, is the responsibility of the user.

It is implicit that the user is responsible for determining appropriate safety measures and for applying the legislation covering his/her own activities.